



NEW

NEW



CONDUCTIVE & STATIC DISSIPATIVE PLASTIC

PLANET 152 ATEX CE EX II 3D Ex t IIIB T135°C Dc IP55

EXCLUSIVE CHARACTERISTICS

- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ BIG AND BRAKED WHEELS
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR
- ▶ LONG LASTING TURBINE WITH PERFECT PERFORMANCE
- ▶ EXPLOSION PROOF TURBINE AND DESIGN FOR ATEX ZONE 22
- ▶ CONDUCTIVE WHEELS WITH BRAKES
- ▶ STATIC DISSIPATING FILTERS
- ▶ CONDUCTIVE POLY LINER BAGS WITH SAFETY STRING
- ▶ PCB PREFILTER & ADDITIONAL CARTRIDGE



CONDUCTIVE & STATIC DISSIPATIVE PLASTIC

PLANET 202 ATEX CE EX II 3D Ex t IIIB T135°C Dc IP55

EXCLUSIVE CHARACTERISTICS

- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ DOUBLE STAGE MOTORS AND TURBINE
- ▶ BIG AND BRAKED WHEELS
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR
- ▶ LONG LASTING TURBINE WITH PERFECT PERFORMANCE
- ▶ EXPLOSION PROOF TURBINE AND DESIGN FOR ATEX ZONE 22
- ▶ CONDUCTIVE WHEELS WITH BRAKES
- ▶ STATIC DISSIPATING FILTERS
- ▶ CONDUCTIVE POLY LINER BAGS WITH SAFETY STRING
- ▶ PCB PREFILTER & ADDITIONAL CARTRIDGE

		PLANET 152 ATEX	
		ASID00379	
Code			
TECHNICAL DATA			
Usage		DRY	
Number of phases		1	
Voltage	V	220-240	
Turbine		1xsingle stage	
Power	W	1500	
Water lift	mmH ₂ O	1800	
Airflow	m ³ /h	220	
Tank Capacity	l	35	
Diameter of inlet	mm	60	
Filtering surface	cm ²	12.000	
Sound Pressure Level	dB(A)	74	
Dimensions (LxWxH)	mm	710x660x1280	
Weight	Kg	62.5	

		PLANET 202 ATEX	
		ASID00412	
Code			
TECHNICAL DATA			
Usage		DRY	
Number of phases		three phase	
Voltage	V	400	
Turbine		1xsingle stage	
Power	W	3000	
Water lift	mmH ₂ O	2500	
Airflow	m ³ /h	304	
Tank Capacity	l	40	
Diameter of inlet	mm	60	
Filtering surface	cm ²	19.500	
Sound Pressure Level	dB(A)	76	
Dimensions (LxWxH)	mm	680x700x1360	
Weight	Kg	60	

STANDARD EQUIPMENT

CODE: KTRI03141 CONDUCTIVE FILTERING KIT
 CODE: FTDP00223 POLYCARBON PREFILTER



STANDARD EQUIPMENT

CODE: KTRI04594 CONDUCTIVE FILTERING KIT
 CODE: FTDP40014 POLYCARBON PREFILTER



OPTIONAL ACCESSORIES

Anti-Static tool kit Ø50-60 mm	PMDT00436
Anti-Static tool kit Ø38-60 mm	PMDT00326
High Reach Cleaning ATEX	-
Hepa cartridge kit	KTRI03681
Nylon filter for exhausting air	FTDP00410
Connection for nylon filter	RCVR00878

OPTIONAL ACCESSORIES

Anti-Static tool kit Ø50-60 mm	PMDT00436
Anti-Static tool kit Ø38-60 mm	PMDT00326
High Reach Cleaning ATEX	-

IP Cleaning S.p.A.

Viale Treviso 63 - 30026 Summaga di Portogruaro (VE) - Italy
 Tel. +39 0421 205511 - Fax +39 0421 204227 - info@ipcworldwide.com - www.ipcworldwide.com