



NEW

NEW



PLANET OIL 2M

PLANET OIL 3M

EXCLUSIVE CHARACTERISTICS

- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ DRAIN HOSE
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ TANGENTIAL OR METAL INLET
- ▶ DOUBLE STAGE MOTORS AND TURBINE
- ▶ BIG AND BRAKED WHEELS
- ▶ QUICK MAINTENANCE FRAMEWORK WITH DETACHABLE TANK
- ▶ SIEVE BASKET & ANTI BLOCK FLOATING SYSTEM
- ▶ ANTISKID WHEELS WITH BRAKES
- ▶ VISUAL FILLING INDICATOR
- ▶ SAFETY VALVES AND DRAIN SYSTEM
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ TANGENTIAL INLET AND CONVEYOR CONE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR

		PLANET OIL 2M	PLANET OIL 3M
Code		ASID00523	ASID00524
TECHNICAL DATA			
Usage		WET & DRY	WET & DRY
Number of phases		single phase	single phase
Voltage	V	220-240	220-240
Frequency	Hz	50-60	50-60
N. and type of motor		2x2 stages	3x2 stages
Power	W	2000-2400 max	3000-3600 max
Water lift	mmH ₂ O	2470	2470
Airflow	m ³ /h	420	630
Tank Capacity	l	100	100
Bucket sieve capacity	l	40	40
Diameter of inlet	mm	60	60
Sound Pressure Level	dB(A)	74	76
Dimensions (LxWxH)	mm	850x650x1350	850x650x1350
Weight	Kg	62	65

STANDARD EQUIPMENT

CODE: KTRI02521
FILTERING KIT (3100 + 1500 CM²)

CODE: FTC000011
NYLON FILTER (PA 200 μ)

CODE: SECC00113
BUCKET SIEVE



OPTIONAL ACCESSORIES

Optional Anti-oil tool kit Ø50-60 mm

PMDT00449

IP Cleaning S.p.A.

Viale Treviso 63 - 30026 Summaga di Portogruaro (VE) - Italy
Tel. +39 0421 205511 - Fax +39 0421 204227 - info@ipcworldwide.com - www.ipcworldwide.com