TOOL PRO WDA 40 L / L AS

VACUUM CLEANERS WITH AUTOMATIC FILTER CLEANING

Large capacity, sturdy and powerful wet and dry vacuum cleaner approved for L class dust. It is specifically designed to work in environments characterized by the presence of simple dust at moderate risk. Compact and manageable, TOOL PRO WDA 40 L is ideal for use in environments such as workshops and artisan laboratories. The innovative NONSTOPVAC! system, thanks to the automatic cleaning of the main filter through the reverse air flow, ensures a constant vacuuming and significantly reduces the downtime, allowing the operator to work without interruptions keeping high suction performance. Equipped with the power outlet for electric tool (max power 2400 W) and COMBI Kit for connecting pneumatic accessories (optional) that ensures an operating pressure of up to 10 bar. The machine can be switched on manually or automatically (controlled by the connected tool) and it is also possible to start the vacuum cleaner directly from the flexible hose thanks to the Remote Control Kit (optional). TOOL PRO WDA 40 L is available in two different versions: with antistatic accessories supplied (L AS version), to protect against any electrostatic charges that may occur during work, and with non-antistatic accessories (L version).





Compact and manageable



Pivoting wheels with brake



Hooks for accessories and cable holder



Power tool connection



NONSTOPVAC!

REF. NO. 13101710001

13201710001



PTFE flat filter

8

8

PIECES/PALLET



Antistatic accessories (standard for L AS version)



COMBI Kit (optional)

PRODUCT IDENTIFICATION

TYPE	
TOOL PRO WDA 40 L	
TOOL PRO WDA 40 L AS	

TECHNICAL DATA

Voltage - Frequency	220-240 V~ 50	/60 Hz
Max power rating	W	1350
Rated power (nominal power)	W	1100
Max power of electrical socket load	W	2400
Main filter	PTFE flat filter (N	filtration class)
Filtering surface (flat filter)	m²	0,5
Filter cleaning system		NONSTOPVAC!
Air flow rate	I/s	76
Vacuum	mbar	250
Container capacity	1	41
Useful capacity	1	26
Useful dust bag capacity	1	20
IP code		IPX4
Filtration class		L
Accessories Diameter	mm	33
Power supply cable	m	7
Weight (without accessories)	Kg	21
Dimensions	mm	625x385x545

STANDARD	ACCESSORIES

TYPE	REF. NO.
Flexible hose Ø 33 - 4 m (*)	6010533
Antistatic flexible hose Ø 33 - 4 m (**)	6010530
Chromed extension tube 0,5 m (***)	2511500
Dry floor tool P340 Ø 36 (*)	6010041
Antistatic dry floor tool P340 Ø 36 (**)	6010042
Connection Ø 33 (*)	2511405
Antistatic connection Ø 33 (**)	2511406
Crevice tool Ø 36 (*)	2511520
Antistatic crevice tool Ø 36 (**)	2511640
Front intake cap	2001817
PTFE flat filter (M filtration class)	2512772
Fleece filter bag (I 20)	

OPTIONAL ACCESSORIES

OI IIOIIAE AGGEGGGIIIEG	
TYPE	REF. NO.
Antistatic flexible hose Ø 29 - 4 m (**)	6010531
Flexible hose Ø 38 - 4 m	6010536
Squeegee tool V340 Ø 36	6010046
COMBI Kit	6689163
Remote Control Kit	6689165
Box adaptors	6689164
Transport handle	6340100
PE bag	3001203
Fleece filter bag I 20 x 10	3001039



(*) For L version (**) For L AS version (***) 2 on standard equipment

TOOL PRO WDA 40 M AS

VACUUM CLEANERS FOR HAZARDOUS DUST WITH AUTOMATIC FILTER CLEANING

Large capacity, sturdy and powerful wet and dry vacuum cleaner approved for M class dust. It is specifically designed to work in environments characterized by the presence of medium-risk dust such as those arising from hardwoods, stucco, paints, concrete. Compact and manageable, TOOL PRO WDA 40 M AS is ideal for use in industrial environments, craftsmen and construction sites. The innovative NONSTOPVAC! system, thanks to the automatic cleaning of the main filter through the reverse air flow, ensures a constant vacuuming and significantly reduces the downtime, allowing the operator to work without interruptions keeping high suction performance. Equipped with the power outlet for electric tool (max power 2400 W) and COMBI Kit for connecting pneumatic accessories (optional) that ensures an operating pressure of up to 10 bar. The machine can be switched on manually or automatically (controlled by the connected tool) and it is also possible to start the vacuum cleaner directly from the flexible hose thanks to the Remote Control Kit (optional). TOOL PRO WDA 40 M AS is available with antistatic accessories supplied, to protect against any electrostatic charges that may occur during work.









Different diameters of selectable accessories



Power tool connection



NONSTOPVAC!



PTFE flat filter

REF. NO.

13301710001



Fleece filter



COMBI Kit (optional)



Antistatic accessories

PRODUCT IDENTIFICATION

TYPE

TOOL PRO WDA 40 M AS

TECHNICAL DATA

Voltage - Frequency	220-240 V~ 50)/60 Hz
Max power rating	W	1350
Rated power (nominal power)	W	1100
Max power of electrical socket load	W	2400
Main filter	PTFE flat filter (N	/I filtration class)
Filtering surface (flat filter)	m²	0,5
Filter cleaning system		NONSTOPVAC!
Air flow rate	I/s	76
Vacuum	mbar	250
Container capacity		41
Useful capacity		26
Useful dust bag capacity	I	20
IP code		IPX4
Filtration class		M
Accessories Diameter	mm	21 - 29 - 33 - 38
Power supply cable	m	7
Weight (without accessories)	Kg	21
Dimensions	mm	625x385x545

STANDARD ACCESSORIES

OTANDAND ACCESSIONES	
TYPE	REF. NO.
Antistatic flexible hose Ø 33 - 4 m	6010530
Chromed extension tube 0,5 m (*)	2511500
Antistatic dry floor tool P340 Ø 36	6010042
Antistatic connection Ø 33	2511406
Antistatic crevice tool Ø 36	2511640
Front intake cap	2001817
PTFE flat filter (M filtration class)	2512772
Fleece filter bag (I 20)	
Antistatic dry floor tool P340 Ø 36 Antistatic connection Ø 33 Antistatic crevice tool Ø 36 Front intake cap PTFE flat filter (M filtration class)	6010042 2511406 2511640 2001817

PIECES/PALLET

OPTIONAL ACCESSORIES

TYPE	REF. NO.
Antistatic flexible hose Ø 29 - 4 m	6010531
Flexible hose Ø 38 - 4 m	6010536
Squeegee tool V340 Ø 36	6010046
COMBI Kit	6689163
Remote Control Kit	6689165
Box adaptors	6689164
Transport handle	6340100
PE bag	3001203
Fleece filter bag I 20 x 10	3001039



TOOL PRO WDA 40 H AS

VACUUM CLEANERS FOR HAZARDOUS DUST WITH AUTOMATIC FILTER CLEANING

Large capacity, sturdy and powerful wet and dry vacuum cleaner approved for H class dust. It is specifically designed to work in high-risk environments characterized by the presence of moulds, pathogens and carcinogenic powders (such as asbestos, cobalt, nickel, lead). Compact and manageable, TOOL PRO WDA 40 HAS is ideal for use in industrial environments, craftsmen and construction sites. The innovative NONSTOPVAC! system, thanks to the automatic cleaning of the main filter through the reverse air flow, ensures a constant vacuuming and significantly reduces the downtime, allowing the operator to work without interruptions keeping high suction performance. Maximum filtration efficiency (99.995 %) thanks to the HEPA cartridge filter. installed on the machine. Equipped with the power outlet for electric tool (max power 2400 W) and COMBI Kit for connecting pneumatic accessories (optional) that ensures an operating pressure of up to 10 bar. The machine can be switched on manually or automatically (controlled by the connected tool) and it is also possible to start the vacuum cleaner directly from the flexible hose thanks to the Remote Control Kit (optional). TOOL PRO WDA 40 H AS is available with antistatic accessories supplied, to protect against any electrostatic charges that may occur during work.



















Large capacity

Control panel

NONSTOPVAC!

PTFE flat filter

HEPA cartridge filter

REF. NO.

13401710001

PE bag (optional)

COMBI Kit (optional)

Antistatic accessories

PRODUCT IDENTIFICATION

TYPE
TOOL PRO WDA 40 H AS

TECHNICAL DATA

Voltage - Frequency	220-240 V~ 50/0	60 Hz
Max power rating	W	1350
Rated power (nominal power)	W	1100
Max power of electrical socket load	W	2400
Main filter	PTFE flat filter (M filtration class) + HEPA cartridge filter (H filtration class)	
Filtering surface (flat filter)	m ²	0,5
Filtering surface (class H cartridge filter)	m²	0,8
Filter cleaning system		NONSTOPVAC!
Air flow rate	I/s	76
Vacuum	mbar	250
Container capacity	1	41
Useful capacity	1	26
Useful dust bag capacity	1	20
IP code		IPX4
Filtration class		Н
Accessories Diameter	mm	21 - 29 - 33 - 38
Power supply cable	m	7
Weight (without accessories)	Kg	21
Dimensions	mm	625x385x545

STANDARD ACCESSORIES

TYPE	REF. NO.
Antistatic flexible hose Ø 33 - 4 m	6010530
Chromed extension tube 0,5 m (*)	2511500
Antistatic dry floor tool P340 Ø 36	6010042
Antistatic connection Ø 33	2511406
Antistatic crevice tool Ø 36	2511640
Front intake cap	2001817
PTFE flat filter (M filtration class)	2512772
HEPA cartridge filter (H filtration class)	6895010
Fleece filter bag (I 20)	

PIECES/PALLET

OPTIONAL ACCESSORIES

REF. NO.	
6010531	
6010536	
6010046	
6689163	
6689165	
6689164	
6340100	
3001203	
3001039	
	6010531 6010536 6010046 6689163 6689165 6689164 6340100 3001203



